

NOT SUITABLE
FOR ACIDS

ik HC XTREM 1.5

Sprayer specially designed to withstand organic solvents and hydrocarbon-derived solvents mixed with acetone, as well as low VOC products. Manufactured with highly resistant materials, it is also suitable for use with vegetable and animal oils, hydrocarbon-based solvents, lubricants and petroleum derivatives. Suitable for applications such as brake cleaning, removal of tar stains from bodywork and tools, cleaning of machinery and engines, application of lubricants, vehicle interior cleaning, degreasing, wood treatments, waterproofing and vehicle dewaxing, etc.



optimal Oils, solvents and most hydrocarbons.

1. Safety valve, set to 4 bar / 58 psi.
2. Adjustable conical metal nozzle.
3. Seals specially resistant to organic solvents and solvent blends from different origins, as well as Low-VOC products.
4. Large filling aperture.
5. Ergonomic design.
6. Strong translucent tank with level indicator.
7. Protective sleeve for valve chamber.
8. Easy assembly and disassembly for maintenance.

IK HC 1.5 XTREM


TOTAL CAPACITY:	1,5 L - 0.39 US gal
USABLE CAPACITY:	1 L - 0.26 US gal
LITRES/MIN. 3 BAR:	0,50 l/min - 0.13 gal/min
GROSS WEIGHT:	0,6 kg - 1.32 lb
NET WEIGHT:	0,46 kg - 1.02 lb
REFERENCE:	81704



iK HC 1.5 / iK HC TR 1

Industrial sprayers especially manufactured with highly resistant materials for use with animal and vegetable oils, hydrocarbon-based solvents, lubricants and petroleum products.

**NOT SUITABLE
FOR ACIDS**



Ergonomic



optimal Solvent-based pesticides, oils, solvents and petroleum by-products.

IK HC 1.5

1. Strong translucent tank with level indicator.
2. Ergonomic design.
3. Wide opening for easy filling.
4. Despressurizable safety valve.
5. Protective sleeve for valve chamber.

IK HC TR 1

1. Strong translucent tank with level indicator.
2. Content identifying system with coloured cards.
3. Base for greater stability.

IK HC 1.5

Set to 2,5 bar (36 psi)
with depressurization option

Adjustable conical nozzle

1,5 L - 50 oz

1 L - 35 oz

0,50 l/min - 0.13 gal/min

0,6 kg - 1.32 lb

0,46 kg - 1.02 lb

81774

VALVE

STANDARD NOZZLES

TOTAL CAPACITY

USABLE CAPACITY

LITRES/MIN. 3 BAR

GROSS WEIGHT

NET WEIGHT

REFERENCE

IK HC TR 1

Adjustable nozzle

1 L - 35 oz

1 L - 35 oz

0,19 kg - 0.41 lb

0,19 kg - 0.41 lb

84174