



BY EXPERTS
FOR EXPERTS



Antigua, 4
20577 Antzuola
Gipuzkoa - Spain

Ph: + 34 943 786 000
iksprayers@goizper.com
www.iksprayers.com

Goizper UK | Goizper Spain | Goizper Portugal | Goizper France | Goizper Central Europe | Goizper North America | Goizper El Salvador |
Goizper Brazil | Goizper Middle East | Goizper Asia | Goizper West Africa | Goizper East Africa |

GOIZPER S. Coop. reserves the right to change the contents and information of the products shown in this catalogue without prior notice. © GOIZPER S. Coop. all rights reserved. The reproduction in whole or in part of the contents, text and/or images of this catalogue is strictly prohibited.

www.iksprayers.com

iK PPF



Paint Protection Film
Window Tinting
Wrapping



IK WINDOW TINTING & PPF



IK PPF LITE

Professional sprayers specially designed for the application of paint protection films, vinyl wrapping, and window tinting.

They offer 2 pressurization methods: manual or electric (optional) using the IK battery compressor.

Designed for PPF professionals who demand superior results, precision, and complete confidence in every application.



www.iksprayers.com



iK WINDOW TINTING & PPF



Adjustable cone nozzle for fine mist or straight jet spraying.

Even fan nozzle for wider spraying.



1. 6 bar (88 psi) Safety release valve. 2. Pressure gauge. 3. Schrader valve for compressed air connector.



4.5 m (14.8 ft) chemical-resistant spiral hose.



1. Includes fine mesh filter. 2. Lance holder for handle.



Premium-grade corrosion free Stainless-Steel tank and pump.



Stable base with foot support while pumping action.



iK WINDOW TINTING & PPF

Power-up your sprayer with optional accessories
18V Battery Compressor.



iK PPF LITE



Adjustable cone nozzle for fine mist or straight jet spraying.



1. Includes fine mesh filter. 2. Lance holder for handle.



1. 3 bar (43.51 psi) Safety release valve. 2. Possibility to connect to iK compressor.



6 m (19.69 ft) chemical-resistant smooth hose.



Translucent tank with a level indicator.



Stable base with foot support while pumping action.

iK WINDOW TINTING & PPF	VALVE	iK PPF LITE
6 bar (88 psi)		3 bar (43.51 psi)
Adjustable conical nozzle and fan	STANDARD NOZZLES	Adjustable conical nozzle
4.5m (14.8 ft) spiral hose. Optional: 6m (19.69 ft) smooth hose.	HOSE	6m (19.69 ft) smooth hose
Included	AIR COMPRESSOR	Optional
15 L - 3.96 US gal	TOTAL CAPACITY	10 L - 2.64 US gal
13 L - 3.5 US gal	USABLE CAPACITY	8 L - 2.11 US gal
5,5 Kg - 12.1 lb	GROSS WEIGHT	3,3 Kg - 6.59 lb
5 Kg - 1 lb	NET WEIGHT	2,95 Kg - 5.66 lb
83371	REFERENCE	82683